

Cartridge housings

Part no.	Nom. length	Cartridge dia.	Connection size	Description	Max pressure kPa	Max temp °C	Flow rate l/m
10-0910	254 mm	65 mm	19 mm (3/4")	FP10M blue bowl	900	52	38
10-0912	254 mm	65 mm	19 mm (3/4")	FP10T clear bowl	900	52	38
10-0914	254 mm	65 mm	25.4 mm (1")	LC1010 white bowl	900	52	60
10-0916	254 mm	65 mm	25.4 mm (1")	LC1010C clear bowl	900	52	60
10-0920	508 mm	65 mm	19 mm (3/4")	FP20M blue bowl	900	52	76

Tandem and triple housings available on request

Maxi plus high capacity cartridge housings							
10-1000	254 mm	115 mm	25.4 mm (1")	MP100 grey bowl	900	52	80
10-1010	254 mm	115 mm	38.1 mm (1-1/2")	MP200 grey bowl	900	52	85
10-1030	508 mm	115 mm	25.4 mm (1")	MP300 grey bowl	900	52	160
10-1040	508 mm	115 mm	38.1 mm (1-1/2")	MP400 grey bowl	900	52	180

All maxi plus housings come with pressure relief button

High temperature cartridge housings							
10-1050	254 mm	65 mm	19 mm (3/4")	HT100 red bowl	1380	93	38

Stainless steel cartridge housings (Brass head)							
10-1100	254 mm	65 mm	12.7 mm (1/2")	SS115 stainless bowl	2070	99	38
10-1110	254 mm	65 mm	19 mm (3/4")	SS120 stainless bowl	2070	99	38
10-1120	254 mm	65 mm	25.4 mm (1")	SS125 stainless bowl	2070	99	38
10-1130	508 mm	65 mm	19 mm (3/4")	SS220 stainless bowl	2070	99	76
10-1140	508 mm	65 mm	25.4 mm (1")	SS225 stainless bowl	2070	99	90

Includes spanner tool, mounting bracket and drain plug

Stainless steel cartridge housings (stainless head)							
10-1150	254 mm	65 mm	19 mm (3/4")	SS120-S stainless bowl	2070	99	38
10-1160	508 mm	65 mm	19 mm (3/4")	SS220-S stainless bowl	2070	99	76
10-1170	254 mm	115 mm	25.4 mm (1")	SS25MP1 stainless bowl	2070	99	90
10-1180	508 mm	115 mm	38.1 mm (1-1/2")	SS40MP2 stainless bowl	2070	99	180

Includes spanner tool, mounting bracket and drain plug

