

# Filter cartridges

Polyspun sediment cartridges						
Part no.	Type	Diameter	Length	Micron size	Max temp °C	Flow rate l/m
10-0001	Polyspun	65 mm	250 mm	1	64	27
10-0005	Polyspun	65 mm	250 mm	5	64	28
10-0010	Polyspun	65 mm	250 mm	10	64	32
10-0025	Polyspun	65 mm	250 mm	20	64	34
10-0050	Polyspun	65 mm	250 mm	50	64	38
10-0077	Polyspun	65 mm	508 mm	1	64	54
10-0079	Polyspun	65 mm	508 mm	5	64	56
10-0081	Polyspun	65 mm	508 mm	10	64	64
10-0083	Polyspun	65 mm	508 mm	20	64	68
10-0085	Polyspun	65 mm	508 mm	50	64	76

Note: cartridge lengths of 762 mm and 1016 mm available on request

Polyspun Maxiplus sediment cartridges						
Part no.	Type	Diameter	Length	Micron size	Max temp °C	Flow rate l/m
10-0160	Polyspun	115 mm	250 mm	1	64	75
10-0162	Polyspun	115 mm	250 mm	5	64	76
10-0166	Polyspun	115 mm	250 mm	20	64	84
10-0168	Polyspun	115 mm	250 mm	50	64	90
10-0180	Polyspun	115 mm	508 mm	1	64	150
10-0182	Polyspun	115 mm	508 mm	5	64	152
10-0186	Polyspun	115 mm	508 mm	20	64	168
10-0188	Polyspun	115 mm	508 mm	50	64	180

Wound sediment cartridges						
Part no.	Type	Diameter	Length	Micron size	Max temp °C	Flow rate l/m
10-0201	Wound	65 mm	250 mm	1	74	26
10-0205	Wound	65 mm	250 mm	5	74	27
10-0210	Wound	65 mm	250 mm	10	74	32
10-0220	Wound	65 mm	250 mm	20	74	38
10-0250	Wound	65 mm	250 mm	50	74	42
10-0200	Wound	65 mm	250 mm	100	74	48
10-0301	Wound	65 mm	508 mm	1	74	52
10-0305	Wound	65 mm	508 mm	5	74	54
10-0310	Wound	65 mm	508 mm	10	74	64
10-0320	Wound	65 mm	508 mm	20	74	76
10-0350	Wound	65 mm	508 mm	50	74	84
10-0400	Wound	65 mm	508 mm	100	74	96

Note: cartridge lengths of 762 mm and 1016 mm available on request



# Filter cartridges

Wound Maxiplus sediment cartridges						
Part no.	Type	Diameter	Length	Micron size	Max temp °C	Flow rate l/m
10-0405	Wound	115 mm	250 mm	1	74	75
10-0410	Wound	115 mm	250 mm	5	74	76
10-0415	Wound	115 mm	250 mm	10	74	79
10-0420	Wound	115 mm	250 mm	20	74	82
10-0425	Wound	115 mm	250 mm	50	74	90
10-0430	Wound	115 mm	508 mm	1	74	150
10-0435	Wound	115 mm	508 mm	5	74	152
10-0440	Wound	115 mm	508 mm	10	74	158
10-0445	Wound	115 mm	508 mm	20	74	164
10-0450	Wound	115 mm	508 mm	50	74	180



Pleated sediment cartridges						
Part no.	Type	Diameter	Length	Micron size	Max temp °C	Flow rate l/m
10-0600	Pleated	65 mm	250 mm	1	63	41
10-0602	Pleated	65 mm	250 mm	5	63	43
10-0606	Pleated	65 mm	250 mm	20	63	45
10-0608	Pleated	65 mm	250 mm	30	63	46
10-0610	Pleated	65 mm	250 mm	50	63	48
10-0612	Pleated	65 mm	250 mm	100	63	52
10-0620	Pleated	65 mm	508 mm	1	63	82
10-0622	Pleated	65 mm	508 mm	5	63	86
10-0626	Pleated	65 mm	508 mm	20	63	90
10-0628	Pleated	65 mm	508 mm	30	63	92
10-0630	Pleated	65 mm	508 mm	50	63	96
10-0632	Pleated	65 mm	508 mm	100	63	104

Note: Cartridge lengths of 762 mm and 1016 mm available on request



Pleated Maxi plus sediment cartridges						
Part no.	Type	Diameter	Length	Micron size	Max temp °C	Flow rate l/m
10-0640	Pleated	115 mm	250 mm	1	63	88
10-0642	Pleated	115 mm	250 mm	5	63	90
10-0644	Pleated	115 mm	250 mm	20	63	94
10-0646	Pleated	115 mm	250 mm	30	63	95
10-0648	Pleated	115 mm	250 mm	50	63	100
10-0650	Pleated	115 mm	250 mm	100	63	110
10-0660	Pleated	115 mm	508 mm	1	63	176
10-0662	Pleated	115 mm	508 mm	5	63	180
10-0666	Pleated	115 mm	508 mm	20	63	190
10-0668	Pleated	115 mm	508 mm	50	63	200
10-0670	Pleated	115 mm	508 mm	100	63	220

Grooved sediment cartridges						
Part no.	Type	Diameter	Length	Micron size	Max temp °C	Flow rate l/m
10-0700	Grooved (white)	65 mm	250 mm	5	120	31
10-0704	Grooved (white)	65 mm	250 mm	50	120	42
10-0706	Grooved (brown)	65 mm	250 mm	5	120	31
10-0712	Grooved (brown)	65 mm	250 mm	125	120	52
10-0720	Grooved (white)	65 mm	508 mm	5	120	62
10-0724	Grooved (white)	65 mm	508 mm	50	120	84
10-0726	Grooved (brown)	65 mm	508 mm	5	120	62
10-0732	Grooved (brown)	65 mm	508 mm	125	120	104



Granular carbon cartridges - with after filter						
10-0500	GC051	65 mm	250 mm	5	52	13
10-0502	GC202	65 mm	508 mm	20	52	27



Granular Maxi plus carbon cartridges - with after filter						
10-0504	GC20MP1	115 mm	250 mm	20	52	32
10-0506	GC20MP2	115 mm	508 mm	20	52	40

Impregnated carbon cartridges - impregnated carbon (light duty)						
10-0510	IC051	65 mm	250 mm	5	52	19

Moulded carbon cartridges - moulded block (medium duty)						
10-0520	MC011	65 mm	250 mm	1	52	16
10-0522	MC051	65 mm	250 mm	5	52	16
10-0526	MC052	65 mm	508 mm	5	52	22

Moulded Maxi plus carbon cartridges - moulded block (medium duty)						
10-0530	MC05MP1	115 mm	250 mm	5	52	40
10-0532	MC05MP2	115 mm	508 mm	5	52	80

Carbon block cartridges - bonded activated carbon (superior duty)						
10-0540	CB951	65 mm	250 mm	0.5	85	15
10-0544	CB051	65 mm	250 mm	5	85	16
10-0546	CB101	65 mm	250 mm	10	85	18
10-0550	CB952	65 mm	508 mm	0.5	85	28
10-0552	CB052	65 mm	508 mm	5	85	30
10-0554	CB102	65 mm	508 mm	10	85	32

Carbon block Maxi plus cartridges - bonded activated carbon (superior duty)						
10-0560	CB95MP1	115 mm	250 mm	0.5	85	20
10-0562	CB05MP1	115 mm	250 mm	5	85	21
10-0564	CB10MP1	115 mm	250 mm	10	85	23
10-0570	CB95MP2	115 mm	508 mm	0.5	85	40
10-0572	CB05MP2	115 mm	508 mm	5	85	41
10-0574	CB10MP2	115 mm	508 mm	10	85	42

